

IMPACT67 compact module, plastic PROFIBUS DP, 16 dig Out

Digital outputs
DO16 - 0.5 A

Image

Vicarious picture

Approvals**Bus technologies****Connections**

Fieldbus	M12, B-coded
Supply sensor-system/actuator	7/8", 5-pole, 2 × max. 9 A
I/O ports	M12, A-coded, 5-pole

Fieldbus

Operating voltage	24 V DC (18...30.2 V DC) EN 61131-2
Modes	Sync- and freeze mode are supported
Transfer rate	to 12 Mbit/s
Addressing	BCD-rotary switch, 3...99

Output

Switching current per output	max. 0.5 A (short-circuit and overload protected)
------------------------------	---

Diagnostic

Communication status	via LED
Monitoring - under voltage	yes
Short circuit and overload	yes

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 05/13

General data

Protection	IP67
Temperature range	0...+55 °C (storage temperature -25...+70 °C)
Mounting method	2 hole screw mounting, compatible with I/O modules of MBV or MVK model range

Commercial data

Net weight	420
Weight unit	gram
Basic unit	pc.
Customs tariff number	85176200
Unit (piece)	1
Minimum order quantity (piece)	1

Comments

For connection cables please see chapter "Field passive"
Housings potted on the back

Dimension drawing

